APPENDIX E

U.S. DEPARTMENT OF ENERGY R&D ON FUEL CELLS FOR TRANSPORTATION: NEW PROJECTS UNDER DOE PRDA

Focused Projects Under New DOE PRDA

R&D Task Organization Objective/

Deliverable

Membrane Foster-Miller Microporous composite PEM

(ASR<0.05 $\Omega \bullet \text{cm}^2,$ <0.1% crossover of gases) /

kW stack

Electrode 3 M Nano-structured electrode

(CO tolerance 100 ppm, 0.1 mg Pt/cm²) /

multi-cell stack

Spectracorp Optimum carbon vilter paper structure and

electrical properties for gas diffusion /

200 m² carbon paper

Focused Projects Under New DOE PRDA

R&D Task Organization Objective/

Deliverable

Bipolar Plate ElectroChem Low-cost, layered plate

(conductivity > 100 S/cm, perm. < 0.1 mA/cm², equiv. /

short stack

IGT Hydrophilic graphite

composite plates (<\$10/kW)/

production line design

Focused Projects Under New DOE PRDA

Objective/ R&D Task Organization

Deliverable

Stack Engineering Energy Partners PEM fuel cell with composite plates /

50-kW reformate capable stack

Goal: 350 W/L Allied Signal

350 W/kg

PEM fuel cell with metal plates / 50-kW reformate capable stack

51% efficiency @ 50 kW

\$100/kW

Analytic Power PEM fuel cells for testing cell

> components / two 3-kW stacks

Focused Projects Under New DOE PRDA

R&D Task Organization Objective/

Deliverable

Fuel Processor Arthur D. Little Fuel-flexible reformer (under

Processor/Stack Integration) /

50-kW POX with PROX

Goal: 600 W/L

600 W/kg

70% efficiency Hydrogen Burner \$30/kW

Technology

Fuel-flexible reformer / 50-kW POX w/advanced

CO cleanup

Natural gas reformer under Office of Building Technologies /

50-kW POX design

Focused Projects Under New DOE PRDA

Objective/ R&D Task Organization Deliverable

Controls/ Allied Signal High efficiency turbo

compressor-expander /

75 g/s unit

Compressor-Expander

Goal: 4 liters, 3 kg, Arthur D. Little

68% efficiency, \$200

Ancilliaries

Advanced scroll

compressor-expander /

75 g/s unit

Vairex Advanced variable displacement

compressor-expander /

80 g/s unit

Meruit High efficiency bearing/

Radial + Thrust Gas Bearing

Focused Projects Under New DOE PRDA

R&D Task Organization Objective/

Deliverable

Processor/Stack Mechanical Fuel flexible integrated

Technology Inc. Integration power system/

50-kw system

Goal: 250 W/L

250 W/kg

International 40% efficiency Fuel-flexible integrated

\$30/kW Fuel Cells power system/ \$150/kg 50-kw system

Focused Projects Under New DOE PRDA

Objective/ R&D Task Organization Deliverable

Hydrogen Thiokol Conformable high-

Storage pressure storage tank / 1.8 kg H₂ @ 5000psi

Goal: 10% wt. H₂

> Thermo Power Chemical hydride -

> > organic slurry H2 system/ 3 kg/h H₂ fueling system